

Wireless Loadshackle

Product information



Wireless loadshackle with low headroom and a load-centering bobbin.

Battery type/life: Loadcell 4 x AA Alkaline/Load cell 1200 hours continuous.

Accuracy: $\pm 1\%$ of applied load.

Frequency: 2.4 GHz.

System range: 700 m.

Data rate: 3 updates per second.

Protection: IP67.

[... Read more](#)


Temperature range: -10°C up to $+50^{\circ}\text{C}$.

Note: Safety factor when used with a load bobbin.

Safety factor: 5:1

Wireless Loadshackle

Blueprint



Technical data

Part code	Code	WLL ton	Resolution kg	A mm	ØB mm	C mm	D mm	E mm	H mm	L mm	N mm	P mm	Weight kg
423500330160	WLS3,25T	3.25	5	26.9	19.1	56.9	16	42.9	106	127.1	17.5	143	2.8
423500650160	WLS6,5T	6.5	5	36.6	25.4	79.7	22.4	58	148	156.5	24.6	173	3.2
423501200160	WLS12T	12	10	51.5	35.1	113	31.8	82.5	210	196	35.1	218	8
423502500160	WLS25T	25	20	73	51	170	44.5	127	313	281	57	293	18
423505500160	WLS55T	55	50	82.5	57	189.5	51	164	348	306	61	317	25