Lifting Solutions Group
Axel Johnson International

Wireless Loadshackle

Product information



Wireless loadshackle with low headroom and a load-centering bobbin.
Battery type/life: Loadcell 4 x AA Alkaline/Load cell 1200 hours continuous.
Accuracy: ±1% of applied load.
Frequency: 2.4 GHz.
System range: 700 m.
Data rate: 3 updates per second.
Protection: IP67.

... *Read more*

Temperature range: -10°C up to +50°C.
Note: Safety factor when used with a load bobbin.

Safety factor: 5:1


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Wireless Loadshackle

Blueprint



Technical data

Part code	Code	WLL ton	Resolution kg	A mm	ØB mm	C mm	D mm	E mm	H mm	L mm	N mm	P mm	Weight kg
423500330160	WLS3,25T	3.25	5	26.9	19.1	56.9	16	42.9	106	127.1	17.5	143	2.8
423500650160	WLS6,5T	6.5	5	36.6	25.4	79.7	22.4	58	148	156.5	24.6	173	3.2
423501200160	WLS12T	12	10	51.5	35.1	113	31.8	82.5	210	196	35.1	218	8
423502500160	WLS25T	25	20	73	51	170	44.5	127	313	281	57	293	18
423505500160	WLS55T	55	50	82.5	57	189.5	51	164	348	306	61	317	25

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved