



Lifting Clamp STSU

Product information



General: For lifting and transporting of steel plates from all positions (horizontal, vertical and sidelong), articulated lifting shackle. The TSU /STSU/TSU-R lifting clamps are equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered. The clamp is locked in closed as well as in open position.

Marking: Working load limit, jaw capacity and CE-marking.

Finish: Yellow painted.

Note: Min. load is 10% of WLL.

Safety factor: 5:1

Part Code	Code	WLL ton	Jaw width mm	S mm	T mm	U mm	V mm	W mm	X mm	Y mm	Weight kg	Delivery time
16.01856200	6 STSU	6	40-90	114	78	523	275	70	78	32	24	15
16.01856300	7.5 STSU	7.5	50-100	111	78	560	312	70	86	32	30	15
16.01855305	9 STSU	9	50-100	111	78	560	312	70	86	32	31	15
16.01856401	12 STSU	12	50-100	152	85	644	344	100	94	48	45	15
16.01966150	15 STSU	15	80-150	224	85	808	450	136	106	48	78	15
16.01966200	20 STSU	20	80-150	249	100	940	640	153	140	71	171	15
16.01966250	25 STSU	25	80-150	249	100	940	640	153	140	71	171	15
16.01966300	30 STSU	30	80-150	249	100	946	645	156	142	71	176.5	15

Blueprint

