



## Eye Grab Hook 8-041, Yoke

### Product information

- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Finish:** Powder coating

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 8

Part Code	Chain diameter mm	WLL ton	A mm	F mm	G mm	K mm	P mm	Weight kg	Delivery time
167084	6	1.12	13	30	8	51	8	0.2	2
167782	7-8	2	15	30	9	60	10	0.3	15
11.208-041-10	10	3.15	20	41	13	84	13	0.6	15
11.208-041-13	13	5.3	25	52	15	102	16	1.4	15
11.208-041-16	16	8	30	57	20	114	20	2.3	15
11.208-041-20	18-22	12.5	36	73	24	132	23	3.9	15
11.208-041-22	22	15	38	70	26	165	26	4.7	15
11.208-041-26	26	21.2	41	100	32	187	29	9.9	15
11.208-041-32	32	31.5	61	127	40	230	37	21.4	15

Blueprint

