Lifting Solutions Group
Axel Johnson International

Bow Shackle

Product information



The bow shackle with screw pin is made of stamped C15 steel with a white zinc finish.

Approved according to Machinery directive 2006/42/EC.

If you need more dimensions, please contact us!

... *Read more*

Material: stamped C15 steel
Marking: CE-mark, Diameter, WLL, Suplier, batch number
Finish: white zinc plating.

Safety factor: 5:1

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Bow Shackle

Blueprint



Technical data

Part code	WLL ton	A mm	C mm	D mm	E mm	G mm	L mm	Weight kg/100pc
420100011142	0.1	8	10	5	5	15	20	2
420100021140	0.16	12	12	6	6	18	24	3
420100031140	0.25	15	16	8	8	24	32	7
420100041140	0.4	18	20	10	10	30	38	13
420100061140	0.63	22	24	12	12	36	50	23
420100081140	0.8	25	28	14	14	42	56	37
420100101140	1	28	32	16	16	48	64	56
420100131140	1.3	35	36	18	18	54	72	78
420100161140	1.6	38	40	20	20	60	80	108
420100201140	2	44	49	22	22	66	85	155
420100251140	2.5	50	57	25	25	75	95	221
420100321140	3.15	54	58	28	27	81	110	298
420100401140	4	68	64	32	31	93	120	417
420100501140	5	75	80	41	38	115	155	770

© November 2026 - All Rights Reserved