

Hoist rope 8 x 19

Product information



General: Elstar 8SF, 8 Strand Fibre Core Hoist Rope


Post Formed & Preformed.

Features: Good Flexibility & Fatigue Properties. Lubricated with T55 in Manufacture.


Marking: According to standard

Finish: Ungalvanised

Standard: EN 12385-5



Elevator



Part code	Rope diameter	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
106100804020179	8	1,570	Bright	sZ	29.4	22.8	SupplierStandard	21.8
106100904020179	9	1,570	Bright	sZ	37.3	28.6	SupplierStandard	27.5
106100954020179	9.5	1,570	Bright	sZ	41.5	31.8	SupplierStandard	30.7
106101004020179	10	1,570	Bright	sZ	46	34.5	SupplierStandard	34
106101104020179	11	1,570	Bright	sZ	55.7	42.4	SupplierStandard	41.1
106101204020179	12	1,570	Bright	sZ	66.2	51.2	SupplierStandard	49
106101304020179	13	1,570	Bright	sZ	77.7	59.8	SupplierStandard	57.5
106101604020179	16	1,570	Bright	sZ	118	89.5	SupplierStandard	87