Lifting Solutions Group
Axel Johnson International

Lever Hoist KITO LB Series

Product information



The KITO LB leverhoist is built with premium grade components and makes it particularly suitable for continuous operation under most severe conditions.

Features:

- Standard supplied with a unique freewheel chain adjusting mechanism with overload protection.
- Rugged and ergonomic lever handle.
- Smooth geared mechanism for effortless handling.
- Robust mechanical load brake increases the safety of the operator.
- Double-reduction gearing requires minimum manual power for operation at full load.
- Open load sheave allows easy inspection and cleaning without dismantling the unit.
- Sealed gears and brake are protected against damage from dust and water.
- Fourfold riveted and forged carbon steel bottom hook.
- Abrasion-resistant nickel-plated load chain V(G100) for high and uniform strength (1000 N/mm^2), in accordance with standard DIN EN 818-7.

Optional:

- Friction clutch
- Overload signal
- Wire rope clip
- Shipyard hooks
- Without freewheel mechanism

... *Read more*

Material: High grade Steel housing, nickel-plated load chain, Carbon steel hooks
Marking: According to standard, CE-mark
Standard: EN 13157
Warning: Minimum load is needed for the load pressure brake to work correct.

Safety factor: 4:1


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lever Hoist KITO LB Series

Blueprint



Technical data

Part code	Code	WLL ton	Lifting height m	Number of falls	Min. load kg	Load chain mm	A mm	B mm	C mm	D mm	e mm	g mm	S mm	t mm	Weight kg
500500080150037	LB008S015	0.8	1.5	1	25	5.6 x 15.7	114	119	280	245	97	23.5	32.5	14	5.7
500500080200030	LB008S020	0.8	2	1	25	5.6 x 15.7	114	119	280	245	97	23.5	32.5	14	6.05
500500080300030	LB008S030	0.8	3	1	25	5.6 x 15.7	114	119	280	245	97	23.5	32.5	14	6.8
500500081050030	LB008S105	0.8	10.5	1	25	5.6 x 15.7	114	119	280	245	97	23.5	32.5	14	12
500500100150030	LB010S015	1	1.5	1	25	5.6 x 15.7	114	119	300	245	97	29	42.5	15	5.9
500500100200030	LB010S020	1	2	1	25	5.6 x 15.7	114	119	300	245	97	29	42.5	15	6.25
500500100300034	LB010S030	1	3	1	25	5.6 x 15.7	114	119	300	245	97	29	42.5	15	7
500500100500030	LB010S050	1	5	1	25	5.6 x 15.7	114	119	300	245	97	29	42.5	15	8.35
500500160150035	LB016S015	1.6	1.5	1	38	7.1 x 19.9	159	126	335	265	100	32	42.5	19	8
500500160200030	LB016S020	1.6	2	1	38	7.1 x 19.9	159	126	335	265	100	32	42.5	19	8.55
500500160300034	LB016S030	1.6	3	1	38	7.1 x 19.9	159	126	335	265	100	32	42.5	19	9.7
500500250150034	LB025S015	2.5	1.5	1	54	8.8 x 24.6	173	150	375	265	102	36.5	47	21	11.2
500500250300030	LB025S030	2.5	3	1	54	8.8 x 24.6	173	150	375	265	102	36.5	47	21	13.8
500500320150030	LB032S015	3.2	1.5	1	35	10.0 x 28.0	190	159	395	415	112	39	50	24.5	15
500500320250030	LB032S025	3.2	2.5	1	35	10.0 x 28.0	190	159	395	415	112	39	50	24.5	17.3
500500320300034	LB032S030	3.2	3	1	35	10.0 x 28.0	190	159	395	415	112	39	50	24.5	18.5
500500321000030	LB032S100	3.2	10	1	35	10.0 x 28.0	190	159	395	415	112	39	50	24.5	34.55
500500630150030	LB063S015	6.3	1.5	2	90	10.0 x 28.0	190	217	540	415	112	50	60	34	26
500500630300034	LB063S030	6.3	3	2	90	10.0 x 28.0	190	217	540	415	112	50	60	34	33.1
500500900150030	LB090S015	9	1.5	3	130	10.0 x 28.0	190	304	680	415	112	72.5	85	41.5	40
500500900300030	LB090S030	9	3	3	130	10.0 x 28.0	190	304	680	415	112	72.5	85	41.5	50.5
500500900350030	LB090S035	9	3.5	3	130	10.0 x 28.0	190	304	680	415	112	72.5	85	41.5	54

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lever Hoist KITO LB Series

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved