

Pump Chain Pewag PCWI Stainless

Product information

Application for submersible pumps and breathers in the water and waste water area.

Material: 1.4404 (AISI 316L), 1.4462 (AISI 318LN).
Finish: Bright polished.

Safety factor: 4:1
Grade: 6

Part Code	WLL ton	Master link	Transition link	Chain type	Shackle jaw space mm	Length of master links/end links mm	Weight SL*	AWI mm	BWI mm	Delivery time
11.6362515	0.32	AWI 6	-	WOX 4x12-5	18	60	0.39	6x60x35	-	15
11.6387067	0.4	AWI 8	BWI 5	WOX 4x12	18	60	0.43	8x60x35	5x26x13	15
11.6387069	0.56	AWI 8	BWI 7	WOX 5x15	25	60	0.62	8x60x35	7x36x16	15
11.6387071	0.63	AWI 10	BWI 7	WOX 5x15	25	80	0.68	10x80x50	7x36x16	15
11.6387073	0.85	AWI 10	BWI 7	WOX 6x18	25	80	0.9	10x80x50	7x36x16	15
11.6387075	1.25	AWI 13	BWI 9	WOX 7x21	25	110	1.35	13x110x60	9x44x20	15
11.6387077	1.6	AWI 13	BWI 10	WOX 8x24	32	110	1.7	13x110x60	10x44x20	15
11.6387079	2.5	AWI 16	BWI 13	WOX 10x30	41	110	2.6	16x110x60	13x54x25	15
11.6387081	3.5	AWI 18	BWI 16	WOX 13X39	56	135	4.5	18x135x75	16x70x34	15
11.6387082	6.3	AWI 22	BWI 20	WOX 16x48	56	160	8	23x160x90	20x85x40	15
11.6330193	8	AWI 26	BWI 22	WOX 20x60	76	180	21	27x180x100	23x115x50	15
11.6330196	12	AWI 45	BWI 32	WOX 26x78	76	340	43.2	45x340x180	32x150x70	15

Blueprint

