

Safety Shackle Pewag SSWI Stainless

Product information

Stainless steel safety shackle, drop-forged, stamped, tested, with added suspension bolt useable as end fitting in chain- and wire rope slings and pump chains for lifting of submersible pumps and breathers, with maximum safety, also under vibration (not directly mountable onto chain).

Material: Stainless steel.
Marking: CE-marked, Article and batch code.

Safety factor: 6:1
Grade: 6

Part Code	Code	WLL ton	a mm	b mm	c mm	d mm	d1 mm	e mm	Weight kg	Delivery time
11.3962074	SSWI 0,63 t-S	0.63	8	18	18	8	9	33	0.07	2
11.3981731	SSWI 0,63 t-S-W	0.63	8	21.5	18	8	9	35	0.08	2
11.3962086	SSWI 0,9 t-S	0.9	10	21.5	22	10	11	41	0.14	2
11.3962090	SSWI 1,6 t-S	1.6	12	26	25	12	13	41	0.22	2
11.3962151	SSWI 2,5 t-S	2.5	15	36	32	15	17	62	0.52	2
11.3962172	SSWI 4,25 t-S	4.25	18	42	46	18	21	78	1	2
11.3962285	SSWI 6,3 t-S	6.3	24	58	59	24	29	109	2.4	2

Blueprint

