



Swivel self locking hooks 8-027

Product information

This hook is positioning device and is not intended to rotate under load.

Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Magnaflux crack detection is performed 100% on each batch.

With Brass Bushing.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Red painted

Standard: EN 1677-3

Safety factor: 4:1

Grade: 8

Part Code	Chain diameter mm	WLL ton	Grade 80 Chain, 1-leg mm	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
167083	6	1.12	6	31	22	12	19	149	29	15	0.7	15
165371	7-8	2	7, 8	36	29	14	24	186	34	20	1.2	2
165372	10	3.15	10	40	34	16	30	220	44	26	2	2
165373	13	5.3	13	46	43	22	39	267	52	30	4.2	15
165374	16	8	16	60	50	24	49	328	60	36	7.3	15
167086	18-20	12.5	18, 20	75	82	26	62	388	90	48	11.7	15
11.158-027-22R	22	15	22	97	95	33	63	457	80	49	18	15
11.158-027-26R	26	21.2	26	123	115	52	69	535	99	56	32	15

Blueprint

