



Eye Self Locking Hook 8-025R

Product information

- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Magnaflux crack detection is performed 100% on each batch.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Red painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	K mm	P mm	A mm	D mm	T mm	H mm	Weight kg
401300110010	6	1.12	110	29	21	10	15	19	0.5
401300200010	7-8	2	136	34	25	11	20	24	0.8
401300320010	10	3.15	167	44	32	13	26	30	1.4
401300530010	13	5.3	207	52	40	16	30	39	2.9
401300800010	16	8	252	60	52	21	36	49	5.7
401301250010	18-20	12.5	282	90	64	23	48	62	8.5
401301500010	22	15	319	80	70	24	49	63	12.5
401302120010	26	21.2	343	99	80	25	56	69	14.5
401302500010	28	25	401	120	90	28	63	81	24.9

Blueprint

