

Flat webbing sling B2



Product information

Flat webbing sling with folded eye. Double ply (B type)

Features: Flexible sling consisting of a single element in sewn webbing.

Material: 100% polyester high tenacity multifilament fibers.

Marking: According to standard, Manufacturer's symbol, working load limit (WLL), effective working length, CE marking, batch number, handling instructions.

Temperature range: From -40°C to +100°C.

Standard: EN 1492-1

Safety factor: 7:1

Part code	EWL m	WLL ton	Thickness mm	Colour	Weight kg
341100100100240	1	1	30	Purple	0.2
341100100200240	2	1	30	Purple	0.4
341100100300240	3	1	30	Purple	0.6
341100100400240	4	1	30	Purple	0.8
341100100500240	5	1	30	Purple	1
341100100600240	6	1	30	Purple	1.2
341100100800240	8	1	30	Purple	1.6
341100200100240	1	2	60	Green	0.4

341100200200240	2	2	60	Green	0.8
341100200300240	3	2	60	Green	1.2
341100200400240	4	2	60	Green	1.6
341100200500240	5	2	60	Green	2
341100200600240	6	2	60	Green	2.4
341100200800240	8	2	60	Green	3.2
341100201000240	10	2	60	Green	4
341100300100240	1	3	90	Yellow	0.55
341100300200240	2	3	90	Yellow	1.1
341100300300240	3	3	90	Yellow	1.65
341100300400240	4	3	90	Yellow	2.2
341100300500240	5	3	90	Yellow	2.75
341100300600240	6	3	90	Yellow	3.3
341100300800240	8	3	90	Yellow	4.4
341100301000240	10	3	90	Yellow	5.5
341100400200240	2	4	120	Grey	1.6
341100400300240	3	4	120	Grey	2.4
341100400400240	4	4	120	Grey	3.2
341100400500240	5	4	120	Grey	4
341100400600240	6	4	120	Grey	4.8
341100400800240	8	4	120	Grey	6.4
341100401000240	10	4	120	Grey	8
341100500200240	2	5	150	Red	2

341100500300240	3	5	150	Red	3
341100500400240	4	5	150	Red	4
341100500500240	5	5	150	Red	5
341100500600240	6	5	150	Red	6
341100500700240	7	5	150	Red	7
341100500800240	8	5	150	Red	8
341100501000240	10	5	150	Red	10
341100501170240	11.7	5	150	Red	11.7
341100600200240	2	6	180	Brown	2.4
341100600300240	3	6	180	Brown	3.6
341100600400240	4	6	180	Brown	4.8
341100600500240	5	6	180	Brown	6
341100600600240	6	6	180	Brown	7.2
341100600800240	8	6	180	Brown	9.6
341100600920240	9.2	6	180	Brown	11.04
341100601000240	10	6	180	Brown	12
341100800300240	3	8	240	Blue	5.1
341100800400240	4	8	240	Blue	6.8
341100800500240	5	8	240	Blue	8.5
341100800600240	6	8	240	Blue	10.2
341100800700240	7	8	240	Blue	11.9
341100800800240	8	8	240	Blue	13.6
341100801000240	10	8	240	Blue	17

341101000300240	3	10	300	Orange	6.75
341101000400240	4	10	300	Orange	9
341101000500240	5	10	300	Orange	11.25
341101000600240	6	10	300	Orange	13.5
341101000800240	8	10	300	Orange	18
341101001000240	10	10	300	Orange	22.5

Blueprint

