
Lifting Solutions Group
Axel Johnson International

# Wire Rope Sling - With Thimbles

## Product information




- Galvanized steel wire rope
- Proof load test at twice the nominal load
- Large opening thimbles up to ø 29 mm
- AFNOR thimbles from ø 32 mm
- Non-deformable reinforced thimbles on request
- Steel wire rope composition and diameter can vary to ensure availability
- The Working load limit (WLL) is calculated according to EN 13414-1 / A1. It can be modified according to the class of resistance of the wire rope used (1770 or 1960 MPa).

... *Read more*

**Marking:** According to standard
**Standard:** EN 13414-1

**Safety factor:** 5:1

**Traction Levage**
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Wire Rope Sling - With Thimbles

## Technical data

| Part code | Rope diameter mm | WLL ton | Construction mm | Tensile Strength (N/mm²) | Thimble Ø mm |
|---|---|---|---|---|---|
| 1603 | 7 | 0.5 | 6 x 19 APP | 1,770 | 31 x 49 |
| 1603 | 8 | 0.65 | 6 x 19 APP | 1,770 | 31 x 49 |
| 1603 | 9 | 0.8 | 6 x 19 APP | 1,770 | 37 x 60 |
| 1603 | 10 | 1 | 6 x 19 APP | 1,770 | 37 x 60 |
| 1603 | 11 | 1.2 | 6 x 19 APP | 1,770 | 43 x 68 |
| 1603 | 12 | 1.4 | 6 x 19 APP | 1,770 | 43 x 68 |
| 1603 | 13 | 1.8 | 6 x 36 APP | 1,770 | 49 x 78 |
| 1603 | 14 | 2.12 | 6 x 36 APP | 1,770 | 49 x 78 |
| 1603 | 16 | 2.7 | 6 x 36 APP | 1,770 | 55 x 87 |
| 1603 | 18 | 3.4 | 6 x 36 APP | 1,770 | 58 x 92 |
| 1603 | 20 | 4.35 | 6 x 36 APP | 1,770 | 62 x 98 |
| 1603 | 22 | 5.2 | 6 x 36 APP | 1,770 | 66 x 105 |
| 1603 | 24 | 6.3 | 6 x 36 APP | 1,770 | 70 x 110 |
| 1603 | 26 | 7.2 | 6 x 36 APP | 1,770 | 73 x 115 |
| 1603 | 29 | 9 | 6 x 36 APP | 1,770 | 81 x 127 |
| 1603 | 32 | 11 | 6 x 36 APP | 1,770 | 72 x 126 |
| 1603 | 34 | 13.5 | 6 x 36 APP | 1,960 | 78 x 137 |
| 1603 | 36 | 15 | 6 x 36 APP | 1,960 | 84 x 147 |
| 1603 | 38 | 17 | 6 x 36 APP | 1,960 | 90 x 158 |
| 1603 | 40 | 19 | 6 x 36 APP | 1,960 | 96 x 168 |
| 1603 | 42 | 22.5 | 6 x 36 SC | 1,960 | 96 x 168 |
| 1603 | 44 | 25 | 6 x 36 SC | 1,960 | 104 x 182 |
| 1603 | 46 | 27 | 6 x 36 SC | 1,960 | 104 x 182 |
| 1603 | 48 | 29.5 | 6 x 36 SC | 1,960 | 112 x 200 |
| 1603 | 52 | 34.5 | 6 x 36 SC | 1,960 | 120 x 210 |
| 1603 | 58 | 43 | 6 x 36 SC | 1,960 | 145 x 258 |
| 1603 | 64 | 55 | 6 x 36 SC | 1,960 | 170 x 290 |
| 1603 | 68 | 65 | 6 x 36 SC | 1,960 | 170 x 290 |
| 1603 | 84 | 100 | 6 x 36 SC | 1,960 | 205 x 338 |


© November 2026 - All Rights Reserved