

# **PULLEY-MAN** portable miniwinch 300kg

### **Product information**

#### General:

• Its motor: your screw driver or drill!

#### Use:

- Light work: maintenance, upkeep, repairs, fitting, installations...
- Small sites
- Agriculture
- First aid
- Mechanized gardening
- Quad
- DIY...

#### Characteristics

- Suspension hook to be easy to set up.
- PULLEY-MAN alone. Available in complete kit version comprising of: a case, a winch, a drill, a charger, a sling and two shackles.
- Small size.
- Light.
- Works in all positions.
- Cable length unlimited in traction.
- Cable length limited to 50 m in lifting (beyond 12 m, loss of 10% of lifting force per 10 m section).
- Automatic load maintenance system (patented self-braking brake reducer).
- Supplied as standard with 12 m of cable (aviation type Ø 4,76 mm.
- Options available: wire rope kit with loop (20 m, 40 m and additional meter), wall support, pulley block to double the load as option (600 kg on two falls when lifting, from 900 to 3000 kg on two falls in hauling depending on the slope).

Part code	WLL	Rope Ø	Weight
	ton	mm	kg
50130003000170	0.3	4 76	7.5

## **Technical data**

### Pulling capacities

Pulling cap. (load on wheels, slope 6°) kg	1500
Pulling cap. (load on wheels, slope 12°) kg	975
Pulling cap. (load on wheels, slope 16°) kg	825
Pulling cap. (load on wheels, slope 27°) kg	585
Pulling cap. (load on wheels, slope 30°) kg	450

# Blueprint

