



Material handling Hoist Red Rooster TCR

Product information

Air chain hoist for material handling 250 kg.

These types Red Rooster Compact pneumatic driven Hoist are very suitable for "Material-Handling". The pendant control is direct on the lower hook so the operator can control and position the load easy and direct. The perfect solution for horizontal movements is the combination with a push trolley.

Standard features:

- Pendant control direct on the lower hook.
- Optimum load control, very precise positioning.
- One-hand control.
- Soft start and stop, no shock movements.
- Handle can be positioned for left-hand or righthand operation.
- Endstop system.

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Marking: CE-marked

| Part code | WLL ton | Lifting height m | Number of falls | Type | Air consumption lifting (l/sec) | Lowering speed with load m/min | Air consumption lowering (l/sec) | Lifting speed with max.load m/min | Weight at 3m HOL kg | Lifting speed without load m/min | A | B | C | D | E | F | G | H | I | J | K | L | M | N | O |
|--------------|---------|------------------|-----------------|-----------|---------------------------------|--------------------------------|----------------------------------|-----------------------------------|---------------------|----------------------------------|-----|-----|-----|-----|----|-----|-----|----|-----|-----|----|-----|----|----|----|
| 5601TCR250ME | 0.25 | 3 | 1 | TCR-250ME | 11.7 | 16 | 13 | 8 | 11 | 19 | 286 | 174 | 112 | 837 | 15 | 194 | 102 | 92 | 184 | 123 | 61 | 152 | 74 | 78 | 36 |

Technical data

Blueprint

