Lifting Solutions Group
Axel Johnson International

Ferrule INOX Talurit®

Product information



These ferrules are normally used on stainless steel wire ropes to achieve the best possible resistance against corrosion.

Stainless steel Ferrule - recommended for machine pressing only. Suitable for long term use in salt water, waste water treatment and chemical processing ... *Read more*

Material: Stainless steel, AISI 316.
Note: See the manufacturer's product data sheet below for guidance on dimension selection. We do not guarantee strength of slings for lifting activities made of INOX ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of the minimum-breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Ferrule INOX Talurit®

Technical data

Part code	Ferrule size mm
120100100110	1
120100150110	1.5
120100200110	2
120100250110	2.5
120100300110	3
120100400110	4
120100500110	5
120100600110	6
120100800110	8
120100900110	9
120101000110	10
120101100110	11
120101200110	12
120101300110	13
120101400110	14
120101600110	16
120101800110	18
120102000110	20
120102200110	22
120102400110	24
120102700110	26

© November 2026 - All Rights Reserved