

## Pillar jib crane, underbraced, 360°: PRT

## **Product information**

Appropriate for an indoor or outdoor use, the beam of the PRT is built on an I beam profile designed for an intensive use. The total rotation is on 360 ° and can be assisted by an engine (optional). The optional installation of a hoist motor direction is possible.

Floor fixing is effected by chemical anchors or anchor rods with foundation.

This model has a wide range of mechanical and electrical options.

## Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind).
- · Motorization on main roller (indoor use).
- Top-mounted motorization (outdoor use).
- · Hoist power supply cable.
- Lockable main switch.
- 4-ring electrical collector, for unlimited rotation.
- Hot dip galvanizing (contact us).
- Rotation stops to weld onto the assembly.
- Single- or multipositions rotation lock.
- · Outdoor use.
- Electric or manual hoist.

WLL ton	Cap. kg	•	Span m 2,5	•					Span m 5,5									Span m 10,0	Span m 10,5	Span m 11,0	Span m 11,5	Span m 12,0	Delivery time
0.15	150	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
0.25	250	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
0.5	500	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
1	1,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
1.6	1,600	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
2	2,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
2.5	2,500	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	15
3.2	3,200	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	15
4	4,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	15
5	5,000	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	15
6.3	6,300	•	•	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	15
8	8,000	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	15
10	10,000	•	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	15