Lifting Solutions Group
Axel Johnson International

Syntethic Lifting Chain Murlink®

Product information



The Murlink® synthetic lifting chain is a soft and strong chain, made from the world's strongest man-made fiber Dyneema®.

Properties:

- Soft, strong, silent and light
- Made from Dyneema®
- Extremely resistant to chemicals, abrasion and cuts
- Minimizes damage to cargo and persons
- Floats on water
- Safe to work with
- Increases efficiency and productivity
- Adjustable length at each link

Fully approved and certified by Applus+ and complies with Machine Directive 2006/42/EC

... *Read more*

Material: UHMWPE Fiber
Marking: CE-mark, Manufacturer ID, WLL, traceability code
Temperature range: -20ºC up to +70ºC

Safety factor: 4:1

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Syntethic Lifting Chain Murlink®

Technical data

Part code	WLL ton	MBL ton	Link size mm	Weight kg
2098102004	2.5	10	100	0.325
2098152006	3.75	15	100	0.475
2098172007	4.375	17.5	100	0.585
2098202008	5	20	100	0.625
2098243006	6	24	125	0.71
2098283007	7	28	125	0.835
2098323008	8	32	125	0.94
2098423010250	10.5	42	250	1.05
2098423010125	10.5	42	125	1.182
2098503013250	12.5	50	250	1.268
2098503013125	12.5	50	150	1.512
2098524010	13	52	250	1.467
2098604011	15	60	250	1.612
2098644012	16	64	250	1.749
2098724013	18	72	250	1.904

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved