

## Syntethic Lifting Chain Murlink®

### Product information



The Murlink® synthetic lifting chain is a soft and strong chain, made from the world's strongest man-made fiber Dyneema®.

#### Properties:

- Soft, strong, silent and light
- Made from Dyneema®
- Extremely resistant to chemicals, abrasion and cuts
- Minimizes damage to cargo and persons
- Floats on water
- Safe to work with
- Increases efficiency and productivity
- Adjustable length at each link

Fully approved and certified by Applus+ and complies with Machine Directive 2006/42/EC

**Material:** UHMWPE Fiber

**Marking:** CE-marked, Manufacturer ID, WLL, traceability code

**Temperature range:** -20°C up to +70°C

**Safety factor:** 4:1

Part Code	WLL ton	MBL ton	Link size mm	Weight kg	Delivery time
-	2.5	10	100	0.325	15
-	3.75	15	100	0.475	15
-	4.375	17.5	100	0.585	15
-	5	20	100	0.625	15
-	6	24	125	0.71	15
-	7	28	125	0.835	15
12.80323008LIFT	8	32	125	0.94	15
12.80423010LIFT	10.5	42	250	1.05	15
-	10.5	42	125	1.182	15
12.80503013LIFT	12.5	50	250	1.268	15
-	12.5	50	150	1.512	15
12.80524010LIFT	13	52	250	1.467	15
-	15	60	250	1.612	15
12.80644012LIFT	16	64	250	1.749	15
12.80724013LIFT	18	72	250	1.904	15