

Syntethic Lashing Chain Murlink®

Product information



The Murlink® synthetic lashing chain is a soft and strong chain, made from the world's strongest man-made fiber Dyneema®.

Properties:

- Soft, strong, silent and light
- Made from Dyneema®
- Extremely resistant to chemicals, abrasion and cuts
- Minimizes damage to cargo and persons
- Floats on water
- Safe to work with
- Increases efficiency and productivity
- Adjustable length at each link

Fully approved and certified by Applus+ and complies with Machine Directive 2006/42/EC

Safety Factor: 2:1

Material: UHMWPE Fiber

Marking: Manufacturer ID, LC, traceability code

Temperature range: -20°C up to +70°C

| Part Code | LC kN | MBL ton | Link size mm | Weight kg | Delivery time |
|-----------------|----------|------------|-----------------|--------------|---------------|
| - | 49 | 10 | 100 | 0.325 | 15 |
| - | 73 | 15 | 100 | 0.475 | 15 |
| - | 85 | 17.5 | 100 | 0.585 | 15 |
| 12.80202008LASH | 98 | 20 | 100 | 0.62 | 15 |
| 12.80243006LASH | 117 | 24 | 125 | 0.71 | 15 |
| 12.80283007LASH | 137 | 28 | 125 | 0.83 | 15 |
| 12.80323008LASH | 156 | 32 | 125 | 0.94 | 15 |
| 12.80423010LASH | 205 | 42 | 125 | 1.2 | 15 |