Lifting Solutions Group
Axel Johnson International

Syntethic Lashing Chain Murlink®

Product information



The Murlink® synthetic lashing chain is a soft and strong chain, made from the world's strongest man-made fiber Dyneema®.

Properties:

- Soft, strong, silent and light
- Made from Dyneema®
- Extremely resistant to chemicals, abrasion and cuts
- Minimizes damage to cargo and persons
- Floats on water
- Safe to work with
- Increases efficiency and productivity
- Adjustable length at each link

Fully approved and certified by Applus+ and complies with Machine Directive 2006/42/EC

Safety Factor: 2:1

... *Read more*

Material: UHMWPE Fiber
Marking: Manufacturer ID, LC, traceability code
Temperature range: -20ºC up to +70ºC

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Syntethic Lashing Chain Murlink®

Technical data

Part code	LC kN	MBL ton	Link size mm	Weight kg
7061102004	49	10	100	0.325
7061152006	73	15	100	0.475
7061172007	85	17.5	100	0.585
7061202008	98	20	100	0.62
7061243006	117	24	125	0.71
7061283007	137	28	125	0.83
7061323008	156	32	125	0.94
7061423010	205	42	125	1.2

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved