Lifting Solutions Group
Axel Johnson International

# Female Double Swivel Ring Codipro SS FE DSR

**Product information**



SS FE DSR M Stainless steel female double swivel ring.

The stainless steel version of the double swivel ring, FE.DSR, can be used in humid, corrosive, chemical, maritime environment. Its double articulation allows it to line up perfectly with the sling.

**Features:**

- Rotatable under load.

... *Read more*

**Material:** AISI 316 L
**Marking:** According to standard, CE-mark
**Temperature range:** -20°C up to + 200°C
**Standard:** EN 1677-1
*except grade/WLL*

**Safety factor:** 5:1


**Traction Levage**
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Female Double Swivel Ring Codipro SS FE DSR

## Blueprint



## Technical data

| Part code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | L max. mm | S mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4215SSFEDSRM8 | 0.3 | M 8 (x1,25) | 6 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 43 | 20 | 0.9 |
| 4215SSFEDSRM10 | 0.5 | M 10 (x1,50) | 10 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 43 | 20 | 0.9 |
| 4215SSFEDSRM12 | 0.8 | M 12 (x1,75) | 15 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 43 | 20 | 0.9 |
| 4215SSFEDSRM14 | 1 | M 14 (x2) | 30 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 43 | 20 | 0.9 |
| 4215SSFEDSRM16 | 1.4 | M 16 (x2) | 50 | 43 | 40 | 45 | 53 | 38 | 17 | 76 | 13 | 43 | 20 | 0.9 |
| 4215SSFEDSRM18 | 1.4 | M 18 (x2,5) | 70 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 62 | 24 | 2.6 |
| 4215SSFEDSRM20 | 1.4 | M 20 (x2,5) | 100 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 62 | 24 | 2.6 |
| 4215SSFEDSRM22 | 2.2 | M 22 (x2,5) | 120 | 62 | 55 | 58 | 83 | 56 | 25 | 115 | 19 | 62 | 24 | 2.6 |


© November 2026 - All Rights Reserved