

## Female Double Swivel Shackle Codipro SS FE DSS

### Product information



Stainless steel female double swivel shackle SS FE DSS.

**Design:** Centered lifting ring with double articulation except for the SEB, swivel eyebolt 360°.

... [Read more](#)

**Material:** AISI 316 L

**Marking:** According to standard, CE-marked, The compliance to EC directives, GRADUP steel quality, The recommended tightening torque, The manufacturer brand, Traceability marks of each component (Blacksmith + batch number), The thread

**Temperature range:** -20°C up to + 200°C


**Finish:** An anti-corrosion coating on the unpainted parts of the CODIPRO swivel lifting points and orange color (RAL 2002) for the schackle.

**Standard:** EN 1677-1  
*except grade/WLL*

**Safety factor:** 5:1

## Female Double Swivel Shackle Codipro SS FE DSS

### Blueprint



### Technical data

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G, mm	L max. mm mm	S mm	Weight kg
4215SSFEDSSM24	2.7	M 24 (x3)	160	66	31	70	98	73	149	30	66	50	5.8
4215SSFEDSSM30	3.5	M 30 (x3.5)	250	66	31	70	98	73	149	30	66	50	5.8
4215SSFEDSSM33	3.5	M 33 (x3.5)	250	66	31	70	98	73	149	30	66	50	5.8
4215SSFEDSSM36	5	M 36 (x4)	320	66	31	70	98	73	149	30	66	50	5.8