
Lifting Solutions Group
Axel Johnson International

# Female Double Swivel Shackle Codipro SS FE DSS

**Product information**



Stainless steel female double swivel shackle SS FE DSS.

**Design:** Centered lifting ring with double articulation except for the SEB, swivel eyebolt 360°.

... *Read more*

**Material:** AISI 316 L
**Marking:** According to standard, CE-mark, The compliance to EC directives, GRADUP steel quality, The recommended tightening torque, The manufacturer brand, Tracebility marks of each component (Blacksmith + batch number), The thread
**Temperature range:** -20°C up to + 200°C
**Finish:** An anti-corrosion coating on the unpainted parts of the CODIPRO swivel lifting points and orange color (RAL 2002) for the schackle.
**Standard:** EN 1677-1
*except grade/WLL*

**Safety factor:** 5:1


**Traction Levage**
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Female Double Swivel Shackle Codipro SS FE DSS

## Blueprint



## Technical data

| Part code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | L max. mm | S mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4215SSFEDSSM24 | 2.7 | M 24 (x3) | 160 | 66 | 31 | 70 | 98 | 73 | 149 | 30 | 66 | 50 | 5.8 |
| 4215SSFEDSSM30 | 3.5 | M 30 (x3.5) | 250 | 66 | 31 | 70 | 98 | 73 | 149 | 30 | 66 | 50 | 5.8 |
| 4215SSFEDSSM33 | 3.5 | M 33 (x3.5) | 250 | 66 | 31 | 70 | 98 | 73 | 149 | 30 | 66 | 50 | 5.8 |
| 4215SSFEDSSM36 | 5 | M 36 (x4) | 320 | 66 | 31 | 70 | 98 | 73 | 149 | 30 | 66 | 50 | 5.8 |


© November 2026 - All Rights Reserved