

## **DYNICE Warp Winch Ropes**

## **Product information**

Specialized high performance rope for extreme deep sea lowering and lifting and towing fishing trawls and it is an excellent choice as winch wire rope replacement.

Dynlce Warp is proven to use on drum winches both in fishing and offshore and is very suitable for traction winches.

**Design:** 6 different layers to make the line with very high cross-sectional stability and axial stiffness. The rope is a heat set and stretched rope with plastic core to ensure firmness and roundness and a durable cover of Dyneema®overbraid is moulded on the main rope. The main strength member and the cover is braided ensuring that the rope is totally balanced and torque free and will not untwist at any load.

Note: The density is 0,96 and the rope is floating but if needed the density can be adjusted up to 1,20 to ensure that the rope is sinking.

Diameter mm	MBL ton	Weight in sea kg	Weight kg/m	Delivery time
12	12	-0.009	0.11	15
14	18	-0.011	0.141	15
16	25	-0.015	0.184	15
18	31	-0.018	0.219	15
20	39	-0.024	0.295	15
22	44	-0.026	0.318	15
24	47	-0.031	0.384	15
26	56	-0.035	0.439	15
28	65	-0.042	0.523	15
30	74	-0.046	0.576	15
32	83	-0.053	0.662	15
34	91	-0.057	0.71	15
36	99	-0.065	0.804	15
38	107	-0.069	0.863	15
40	115	-0.073	0.915	15
42	134	-0.079	0.979	15
44	142	-0.084	1.043	15
46	146	-0.093	1.155	15
48	157	-0.099	1.229	15
50	169	-0.105	1.311	15