

DYNICE Warp Winch Ropes

Product information



Specialized high performance rope for extreme deep sea lowering and lifting and towing fishing trawls and it is an excellent choice as winch wire rope replacement. Dynlce Warp is proven to use on drum winches both in fishing and offshore and is very suitable for traction winches.

Design: 6 different layers to make the line with very high cross-sectional stability and axial stiffness. The rope is a heat set and stretched rope with plastic core to ensure firmness and roundness and a durable cover of Dyneema® overbraid is moulded on the main rope. The main strength member and the cover is braided ensuring that the rope is totally balanced and torque free and will not untwist at any load.

[... Read more](#)

Note: The density is 0,96 and the rope is floating but if needed the density can be adjusted up to 1,20 to ensure that the rope is sinking.

DYNICE Warp Winch Ropes

Technical data

Part code	Diameter mm	MBL ton	Weight in sea kg	Weight kg/m
301201200000150	12	12	-0.009	0.11
301201400000150	14	18	-0.011	0.141
301201600000150	16	25	-0.015	0.184
301201800000150	18	31	-0.018	0.219
301202000000150	20	39	-0.024	0.295
301202200000150	22	44	-0.026	0.318
301202400000150	24	47	-0.031	0.384
301202600000150	26	56	-0.035	0.439
301202800000150	28	65	-0.042	0.523
301203000000150	30	74	-0.046	0.576
301203200000150	32	83	-0.053	0.662
301203400000150	34	91	-0.057	0.71
301203600000150	36	99	-0.065	0.804
301203800000150	38	107	-0.069	0.863
301204000000150	40	115	-0.073	0.915
301204200000150	42	134	-0.079	0.979
301204400000150	44	142	-0.084	1.043
301204600000150	46	146	-0.093	1.155
301204800000150	48	157	-0.099	1.229
301205000000150	50	169	-0.105	1.311