Lifting Solutions Group
Axel Johnson International

PRIMA ropes

Product information

High performance 12 strand braided HMPE rope made from DSM fibres. It has very good breaking strength and good wear.

... *Read more*



Material: HMPE fiber
Temperature range: Maks. 60°C
Finish: Yellow with blue strand

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

PRIMA ropes

Technical data

Part code	Diameter mm	MBL ton	Weight kg/220m
301200600000120	6	4	2.3
301200800000120	8	6.7	3.9
301201000000120	10	10.7	6.2
301201200000120	12	16	9.3
301201400000120	14	18.7	10.3
301201600000120	16	24.9	13.8
301201800000120	18	31	17.2
301202000000120	20	40.1	22.4
301202200000120	22	46.1	25.8
301202400000120	24	55.1	31
301202600000120	26	61.1	34.4
301202800000120	28	67.8	40.2
301203000000120	30	79.8	47.5
301203200000120	32	91.8	54.8
301203400000120	34	103.7	62.1
301203600000120	36	115.5	69.4
301203800000120	38	127.2	76.7
301204000000120	40	138.8	84
301204200000120	42	144.3	87.6
301204400000120	44	167.7	102.2
301204600000120	46	179.1	109.5
301204800000120	48	190.3	116.8
301205000000120	50	201.5	124.1
301205200000120	52	224.3	138.7
301205400000120	54	247.1	153.3

© November 2026 - All Rights Reserved