

Tie rod wall jib crane

Product information



Standard capacity : 150 kg to 2 tons.

- Slewing range 180°.
- Paint RAL 1028.
- With wall brackets. Check the support (column or wall) intended to receive the jib cranes.

Options:

- Equipped with a manual chain hoist.
- Equipped with an electric hoist.
- Other RAL paint available.
- Hotdipped galvanisation.
- Motorised slew.
- Rotation stoppers.
- Slewing retarder.
- Specific fixing systems.
- Other capacities.

[... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 13001-1

Safety factor: 1.5:1

Tie rod wall jib crane

Technical data

| Part code | WLL ton | Radius | Lifting speed m/min. |
|-----------|---------|--------|----------------------|
| 6025 | 0.15 | 2-4-6 | 8,0/2,0 |
| 6025 | 0.25 | 2-4-6 | 8,0/2,0 |
| 6025 | 0.5 | 2-4-6 | 8,0/2,0 |
| 6025 | 1 | 2-4-6 | 4,0/1,0 |
| 6025 | 1.6 | 2-4-6 | 5,0/1,25 |
| 6025 | 2 | 2-4-6 | 5,0/1,25 |
| 6025 | 2.5 | 2-4-6 | 4,0/1,0 |
| 6025 | 3 | 2-4-6 | 4,0/1,0 |
| 6025 | 4 | 2-4-6 | 5,0/1,25 |