Lifting Solutions Group
Axel Johnson International

Tie rod wall jib crane

Product information



Standard capacity : 150 kg to 2 tons.

- Slewing range 180°.
- Paint RAL 1028.
- With wall brackets. Check the support (column or wall) intended to receive the jib cranes.

Options:

- Equipped with a manual chain hoist.
- Equipped with an electric hoist.
- Other RAL paint available.
- Hotdipped galvanisation.
- Motorised slew.
- Rotation stoppers.
- Slewing retarder.
- Specific fixing systems.
- Other capacities.

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13001-1

Safety factor: 1.5:1

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Tie rod wall jib crane

Technical data

Part code	WLL ton	Radius	Lifting speed m/min.
6025	0.15	2-4-6	8,0/2,0
6025	0.25	2-4-6	8,0/2,0
6025	0.5	2-4-6	8,0/2,0
6025	1	2-4-6	4,0/1,0
6025	1.6	2-4-6	5,0/1,25
6025	2	2-4-6	5,0/1,25
6025	2.5	2-4-6	4,0/1,0
6025	3	2-4-6	4,0/1,0
6025	4	2-4-6	5,0/1,25

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved