

Lifting Eye Nut DIN 582 Stainless steel

Product information

Stainless steel lifting eye.

Different angles of inclination.

Material: AISI 316

Marking: CE-marked, WLL, material, supplier name, lifting angle, tracking lot number

Finish: Polished

Safety factor: 6:1



Part code	WLL ton	Thread mm	WLL 90° ton	WLL 0-45° ton	A mm	B mm	C mm	E mm	F mm	G mm	H mm	D mm	Weight kg
421100010392	0.09	M6	0.045	0.06	20	36	20	8.5	8	10	36	M6	0.06
421100140390	0.14	M8	0.07	0.1	20	36	20	8.5	8	10	36	M8	0.05
421100230390	0.23	M10	0.115	0.17	25	45	25	10	10	12	45	M10	0.1
421100340390	0.34	M12	0.17	0.24	30	54	30	11	12	14	53	M12	0.16
421100050390	0.49	M14	0.25	0.35	35	63	35	13	14	16	62	M14	0.16
421100070390	0.7	M16	0.35	0.5	35	63	35	13	14	16	62	M16	0.24
421100120390	1.2	M20	0.6	0.86	40	72	40	16	16	19	71	M20	0.38
421100180390	1.8	M24	0.9	1.29	50	90	50	20	20	24	90	M24	0.77
421100320390	3.2	M30	1.6	2.3	60	108	65	25	24	28	109	M30	1.6

Blueprint

