

## Lifting Eye Bolt DIN 580 Stainless steel



### Product information

Stainless steel lifting eye.

Different angles of inclination.

**Material:** AISI 316

**Marking:** CE-marked, WLL, material, supplier name, lifting angle, tracking lot number

**Finish:** Polish

**Safety factor:** 6:1

Part code	WLL ton	Thread mm	WLL 90° ton	WLL 0-45° ton	A mm	B mm	C mm	E mm	F mm	G, mm	H, mm	L mm	D, mm	Weight kg
421100010372	0.09	M6	0.045	0.06	20	36	20	6	8	10	36	13	M6	0.05
421100140370	0.14	M8	0.07	0.1	20	36	20	6	8	10	36	13	M8	0.06
421100230370	0.23	M10	0.115	0.17	25	45	25	8	10	12	45	17	M10	0.12
421100340370	0.34	M12	0.17	0.24	30	54	30	10	12	14	53	20.5	M12	0.18
421100050370	0.49	M14	0.245	0.35	35	63	35	12	14	16	62	27	M14	0.19
421100070370	0.7	M16	0.35	0.5	35	63	35	12	14	16	62	27	M16	0.31
421100930370	0.93	M18	0.465	0.65	40	72	40	14	16	19	71	30	M18	0.4
421100120370	1.2	M20	0.6	0.86	40	72	40	14	16	19	71	30	M20	0.44
421100180370	1.8	M24	0.9	1.29	50	90	50	18	20	24	90	36	M24	0.94
421100320370	3.2	M30	1.6	2.3	60	108	65	22	24	28	109	45	M30	1.8

# Blueprint

