

## ACX Power Ascender, Skylotec

### Product information



The Skylotec ACX Power Ascender is an ultra-light weight ascender for a very broad range of applications such as rope access work on- and off shore, wind industry, window cleaning, rescue, etc.

For use on superstatic rope  $\varnothing$  11mm according to EN 1891-A

#### Features:

- Easy to connect on and disconnect off ropes.
- Height reach 200 mtrs, with 200 kgs load.  
This is dependent on temperature and load weight, and with lesser weight longer distances are possible, up to 500 mtrs.
- Speed of lifting/descending: adjustable 0 – 24 m/minute.
- Water- and dust resistant class IP-55.
- For persons / loads to max. 200 kgs.
- Weight 13kgs, incl. battery (2,5 kgs).

**European Machine Directive for loads:** 2006/42/EC

[... Read more](#)

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to 40°C

**Standard:** EN 1808, EN 14492, EN 61000

**Note:** Temperature range for best performance: +10°C tot +35°C and Extreme temperature range for safe operation: -20°C tot +40°C

**Warning:** For safe and effective work with the ACX Power Ascender you need specific training, which must be refreshed periodically.

## ACX Power Ascender, Skylotec

### Technical data

Part code	Size	Max. number of persons	Rated load kg	Abseiling height m	Weight kg
824500000290	330 x 280 x 270 mm	1	200	200	13