



Aluminium Hollow Plunger Cylinder HAHC H

Product information

Holmatro aluminum hollow plunger cylinders (HAHC) - Spring or hydraulic return

Unique specifications:

- Up to 60% lighter compared to steel cylinders - easy & ergonomic
- Compact design and a lower build-in
- Suitable for pulling, lifting, tensioning in all positions
- Duo power ring; a combination of a superior seal and an extremely strong composite bearing for a longer life span
- The plunger is coated with a hardened anodized layer, which makes it extremely wear & corrosion resistant

Standard supplied with:

- High flow female coupler A118
- Hollow saddle; prevents damage to the plunger
- Larger cylinders are equipped with foldable handles for easy carrying and positioning

Also available:

- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

Material: Aluminium

Code	WLL ton	stroke length mm	Closed height mm	required oil cc	Weight kg	Delivery time
HAHC100H5	100	50	229	415	28.2	15
HAHC100H10	100	100	279	831	34	15
HAHC100H15	100	150	329	1,246	39.7	15
HAHC100H20	100	200	379	1,661	45.4	15
HAHC100H25	100	250	429	2,076	51.2	15
HAHC150H5	150	50	247	471	41	15
HAHC150H10	150	100	297	942	48.5	15
HAHC150H15	150	150	347	1,414	56	15
HAHC150H20	150	200	397	1,885	63.5	15
HAHC150H25	150	250	447	2,356	71	15

Blueprint

