Lifting Solutions Group
Axel Johnson International

Master Link Assembly MA POWERTEX

Product information



The POWERTEX Master Link Assembly MA is a welded master link assembly used as the top ring in three- and four-leg chain sling assemblies. As part of the POWERTEX Grade 10 lifting chain component range, it provides a reliable connection point

Available for 6 mm up to 22 mm chain and from WLL 3t up to WLL 40t.
All models are welded.

Best used for

- Three-leg and four-leg Grade 10 chain sling assemblies.
- Industrial lifting and rigging applications requiring a welded master link assembly.

Product benefits

- Grade 10 design delivers 25% higher capacity than traditional Grade 8 components.
- Welded construction provides a durable and reliable lifting connection.
- Conforms to EN 1677 Parts 1, 2, 3, and 4 with 25% increased WLL.
- Forged components are crack detection tested, with samples proof load tested for quality assurance.
- Factory type tested and fatigue rated to 20,000 cycles at 1.5 × WLL.
- Batch number traceability and a POWERTEX 2.2 certificate support inspection and documentation.
- The components may also be used with a Grade 8 chain to EN 818-2. In such a case, the chain sling must be rated to Grade 8 in accordance with EN 818-4

... Read more

Marking: According to standard, POWERTEX + Model (MA-6-10) + traceability code.
Temperature range: -40 °C upp till +200 °C utan reduktion av WL
Finish: Powder painted in red
Standard: EN 1677-4 (+25% WLL) , AS 3776
Note: All models are welded


Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Master Link Assembly MA POWERTEX

Blueprint



Technical data

Part code	Code	WLL ton	For chain, 3-4-leg mm	A mm	B mm	D mm	a mm	b mm	d mm	H mm	S mm	Weight kg
402100300770	MA-6-10	3	6	135	75	18	54	25	14	28	7	1.3
402100530770	MA-8-10	5.3	8	160	90	22	70	34	16	28	8	2.2
402100840770	MA-10-10	8.4	10	180	100	27	85	40	18	28	11	3.6
402101400770	MA-13-10	14	13	200	110	33	115	50	22	43	13	6.4
402102120770	MA-16-10	21.2	16	260	140	36	140	65	28	55	17	10.6
402103360770	MA-20-10	33.6	20	350	190	50	180	90	32	-	-	23.7
402104000770	MA-22-10	40	22	350	190	50	180	100	36	-	-	26

© November 2026 - All Rights Reserved