



Eye Nut C802

Product information

Eye nut to be screwed by hand.

Material: Alloy steel 8.8.

Marking: Marked with WLL, sizes, steel quality, CE, producername, tracability.

Finish: Red painted.







Note: Approved for lifting.

Safety factor: 4:1

| Part code | WLL ton | Thread mm | A, | B, | C, | E, | F, | H, | Weight kg |
|--------------|------------|--------------|----|-----|----|----|----|-----|--------------|
| 421100040120 | 0.4 | M6 | 25 | 45 | 25 | 10 | 10 | 45 | 0.1 |
| 421100080120 | 0.8 | M8 | 25 | 45 | 25 | 10 | 10 | 45 | 0.1 |
| 421100100120 | 1 | M10 | 25 | 45 | 25 | 10 | 10 | 45 | 0.1 |
| 421100160120 | 1.6 | M12 | 35 | 63 | 35 | 14 | 14 | 62 | 0.26 |
| 421100300120 | 3 | M14 | 35 | 63 | 35 | 14 | 14 | 62 | 0.26 |
| 421100400120 | 4 | M16 | 35 | 63 | 35 | 14 | 14 | 62 | 0.26 |
| 421100500120 | 5 | M18 | 50 | 90 | 50 | 20 | 20 | 90 | 0.75 |
| 421100600120 | 6 | M20 | 50 | 90 | 50 | 20 | 20 | 90 | 0.75 |
| 421100800120 | 8 | M24 | 50 | 90 | 50 | 20 | 20 | 90 | 0.75 |
| 421101000120 | 10 | M27 | 60 | 108 | 65 | 24 | 24 | 109 | 1.4 |
| 421101200120 | 12 | M30 | 60 | 108 | 65 | 24 | 24 | 109 | 1.4 |

Technical data

Working load limit W.L.L. (t)

| Code | Size mm | 0° 1 leg | 0° 2 legs | 0°- 45° 2 legs | 45°- 60° 2 legs | 0°- 45° 3/4 legs | 45°- 60° 3/4 legs | Max tightening torque Nm |
|--------|------------|---|---|---|---|---|---|-----------------------------------|
| | |  |  |  |  |  |  | |
| C80206 | M6 | 0,4 | 0,8 | 0,14 | 0,1 | 0,2 | 0,14 | 3,5 |
| C80208 | M8 | 0,8 | 1,6 | 0,28 | 0,2 | 0,4 | 0,28 | 8 |
| C80210 | M10 | 1 | 2 | 0,35 | 0,25 | 0,5 | 0,35 | 16 |
| C80212 | M12 | 1,6 | 3,2 | 0,56 | 0,4 | 0,8 | 0,56 | 28 |
| C80214 | M14 | 3 | 6 | 1 | 0,75 | 1,5 | 1 | 45 |
| C80216 | M16 | 4 | 8 | 1,4 | 1 | 2 | 1,4 | 70 |
| C80218 | M18 | 5 | 10 | 1,8 | 1,25 | 2,5 | 1,8 | 95 |
| C80220 | M20 | 6 | 12 | 2,1 | 1,5 | 3 | 2,1 | 135 |
| C80224 | M24 | 8 | 16 | 2,8 | 2 | 4 | 2,8 | 230 |
| C80227 | M27 | 10 | 20 | 3,5 | 2,5 | 5 | 3,5 | 343 |
| C80230 | M30 | 12 | 24 | 4,2 | 3 | 6 | 4,2 | 465 |

Blueprint

