

Turnbuckle Eye and Hook DIN 1480

Product information

Turnbuckle for tightening ropes.

... [Read more](#)



Material: Fe-430 b Steel


Marking: According to standard, CE-marked

Standard: DIN 1480

Warning: Do not use for lifting.

Turnbuckle Eye and Hook DIN 1480

Blueprint



Technical data

| Part code | Length range | Thread | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | L1 mm | L2 mm | Weight kg |
|--------------|--------------|--------|------|------|------|------|------|------|------|------|-------|-------|-----------|
| 492122600570 | 140-226 | M6 | 12 | 110 | 74 | 50 | 10 | 76 | 50 | 8 | 140 | 226 | 0.09 |
| 492123500570 | 155-235 | M8 | 15 | 110 | 80 | 52 | 11 | 89 | 52 | 10 | 155 | 235 | 0.14 |
| 492127300570 | 185-273 | M10 | 18 | 125 | 97 | 60 | 14 | 103 | 62 | 13 | 185 | 273 | 0.28 |
| 492129000570 | 208-290 | M12 | 21 | 125 | 106 | 67 | 17 | 121 | 65 | 17 | 208 | 290 | 0.41 |
| 492134400570 | 248-344 | M14 | 24 | 140 | 126 | 83 | 18 | 144 | 82 | 14 | 248 | 344 | 0.57 |
| 492141900570 | 303-419 | M16 | 27 | 170 | 160 | 97 | 23 | 168 | 100 | 16.5 | 303 | 419 | 0.96 |
| 492147300570 | 341-473 | M20 | 34 | 200 | 190 | 116 | 25 | 185 | 110 | 17 | 341 | 473 | 1.54 |
| 492152700570 | 379-527 | M22 | 36 | 220 | 200 | 120 | 30 | 216 | 125 | 22 | 379 | 527 | 2.13 |
| 492156800570 | 391-568 | M24 | 39 | 255 | 210 | 125 | 34 | 225 | 125 | 23 | 391 | 568 | 2.84 |
| 492160200570 | 437-602 | M27 | 45 | 255 | 236 | 150 | 34 | 250 | 146 | 29 | 437 | 602 | 3.89 |
| 492160400570 | 439-604 | M30 | 45 | 255 | 242 | 150 | 39 | 250 | 140 | 30 | 439 | 604 | 4.15 |
| 492162600570 | 441-626 | M33 | 55 | 295 | 242 | 150 | 39 | 250 | 140 | 30 | 441 | 626 | 5.88 |
| 492168200570 | 497-682 | M36 | 55 | 295 | 276 | 165 | 49 | 288 | 170 | 30 | 497 | 682 | 7.53 |
| 492170900570 | 505-709 | M39 | 63 | 330 | 276 | 165 | 49 | 288 | 170 | 30 | 505 | 709 | 9.38 |