Lifting Solutions Group
Axel Johnson International

Hydraulic Toe Jack HYDROFOR™

Product information



- Robust construction with a block steel body
- Ergonomic and removable handle for transport
- Working load applied on toe and head
- Pressure valve to avoid overloading
- Toe can swivel 360° around the axis of the jack
- Operation in both vertical and horizontal position.
- Easy maintenance
- Removable operating lever

... *Read more*

Marking: CE-mark
Warning: Do not use in unstable and uncertain positions. Never subject the toe to point loading, always fully load.


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Hydraulic Toe Jack HYDROFOR™

Blueprint



Technical data

Part code	WLL ton	Hand force max. kg	Min–max lifting height of toe mm	Min–max lifting height of top mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg
5205243269	5	38	25 - 230	368 - 573	368	740	140	213	ø 93	25	205	20
5205243279	10	40	20 - 260	420 - 650	420	745	170	205	ø 103	30	230	28
520579909	25	40	58 - 273	505 - 720	505	1,305	210	420	155 x 155	58	215	109

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved