Lifting Solutions Group
Axel Johnson International

Flexible Lanyard POWERTEX FL-1

Product information



The Powertex FL-1 flexible lanyard is equipped with a shock absorber and is approved for 140 kg use. This lanyard is elastic, allowing it to stretch per the user's movements. The lanyard is securely sewn to a shock absorber pack, which includes a screw gate steel carabiner for attachment to a harness. Sewn-in double-action aluminum scaffold hooks provide reliable anchorage on the other end of the lanyards.

In the unlikely event of a fall, the shock absorber pack will rupture to absorb the energy of the fall. If this happens it reveals a white webbing that serves as a fall indicator. This feature lets users quickly identify if a lanyard has been used in a fall and must be removed from service.

The FL-1 flexible lanyard is manufactured to the highest standards and is designed to provide reliable fall protection for those who work at heights. It's also RFID-equipped (HF 13,56 MHz chip) for easy service, inspection, and asset control.

Carabiner: Screw gate carabiner (23 kN) acc to EN 362 marked with serial number
Scaffold hooks: Double action scaffold hook with eye (23kN) acc to EN 362 with 60 mm opening.
Hand washing: Allowed up to +40°C with mild detergent.

... *Read more*

Features: CE & UKCA approved.
Material: Polyester lanyard, Polyester shock absorber, Steel carabiner, Aluminum scaffold hooks
Marking: According to standard, CE-mark, UKCA-marked, Supplier symbol, Product identification, Max weight, Length (Nom), Length (Max), Production date, Serial number.
Temperature range: -35°C up to +50°C
Standard: EN 355

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Flexible Lanyard POWERTEX FL-1

Technical data

Part code	Length m	Max load kg	Weight kg
821100142310	1.4	140	1

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved