

Corner Protector Extreema®

Product information



The Extreema® Corner Protector is an essential accessory for repetitive lifting operations involving payloads with sharp or abrasive edges. Specifically engineered to safeguard your equipment, it is crafted from HMPE or Dyneema®, This ensures maximum durability and a significantly longer lifespan for your round slings and lifting gear, even in the most demanding industrial environments.

Designed for flexibility and ease of use, the Extreema® Corner Protector features two integrated Velcro® straps that allow quick and secure attachment to the sling. This user-friendly design enables fast installation and repositioning, ideal for dynamic work environments where efficiency matters.

By integrating the Extreema® Corner Protector into your lifting operations, you minimize sling wear, reduce the risk of equipment damage, and significantly lower the need for maintenance or replacement. It's a smart investment in safety, longevity, and operational efficiency.

When to choose this product

Best for:

- Lifting loads with sharp edges or rough surfaces
- Repetitive operations where sling wear is a concern

Product benefits:

- Extreme abrasion, cut, puncture, and tear resistance
- High dynamic toughness and flex fatigue resistance
- Exceptional flexibility for use on various angles and surfaces
- Equipped with secure Velcro® straps for fast attachment
- Lightweight and easy to install or remove
- Significantly extends the service life of lifting slings

... [Read more](#)

Material: 100% Dyneema®

Marking: According to standard, Extreema® protect

Temperature range: -40°C up to +70°C

Standard: EN 1492-2

except material

Corner Protector Extreema®

Technical data

| Part code | Length mm | Band width mm | Thickness mm | For roundslings ton |
|----------------|--------------|------------------|-----------------|---------------------|
| 8005EXCP85500 | 500 | 75 | 12 | 1-6 |
| 8005EXCP115500 | 500 | 100 | 12 | 8 |
| 8005EXCP135500 | 500 | 120 | 12 | 10-12 |
| 8005EXCP160500 | 500 | 150 | 12 | 15 |
| 8005EXCP190600 | 600 | 180 | 12 | 10-15 |
| 8005EXCP230800 | 800 | 200 | 12 | 30-40 |
| 8005EXCP260800 | 800 | 240 | 12 | 45 |
| 8005EXCP290800 | 800 | 240 | 12 | 50-55 |