



Lifting Belt Sling

Product information

The Lift-Tex® lifting belt sling is a wide-body lifting sling designed for handling heavy loads up to 100 tonnes. It is used in applications where increased surface contact, load stability, and reduced wear are critical. Manufactured from HMPE and polyester, it combines high strength with controlled load distribution for demanding lifting operations.

WLL range: 10t – 100t

EWL range: 0,5m – 65m

When to choose this product

Best for:

- Lifting heavy loads requiring increased surface contact and stability
- Applications where reduced surface pressure and sling wear are important

Product benefits

- Wide body design improves load distribution and lifting stability
- HMPE and polyester core delivers high strength and durability
- Reinforced soft eyes support secure and efficient hook connection
- Optional protective sleeves increase resistance to cuts and abrasion
- Multi-channel construction enhances control during lifting operations

Material: HMPE and Polyester

Marking: According to standard, Label in a reinforced plastic seal.

Standard: EN 1492-1

Standard: EN 1492-2

except material

Safety factor: 7:1

Part code	WLL ton	Width mm	Eye length mm	Colour
342101000000020	10	240-260	700	Orange
342101500000020	15	240-260	700	Orange
342102000000020	20	350-400	700	Orange
342102500000020	25	350-400	700	Orange
342103000000020	30	350-400	700	Orange
342104000000020	40	450-500	700	Orange
342105000000020	50	450-500	700	Orange