

The Original Roundsling Extreema® with Dyneema® core



Product information

The Original EXTREEMA® round sling was the first product created under the EXTREEMA® brand. With its innovative design and unparalleled performance, the Original quickly gained a reputation as a top-of-the-line product in the market, paving the way for the brand's continued success and growth.

Its core is made of Bio-Based Dyneema®, which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is white HMPE Extreema® L-series sleeve. With exceptional performance against cuts, abrasions, and punctures. The white sleeve is repairable.

Features:

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Resistant against chemicals
- Does not absorb water
- Floats on water
- Long life cycle
- Sustainable
- WLL: 3t - 600t
- EWL: 0,5m – 65m

Material: Dyneema, HMPE

Marking: According to standard, CE-marked

Temperature range: -50°C up to +70°C

Standard: EN 1492-2

Safety factor: 7:1

Part code

**WLL
ton**

340500300400010

3

340500400300010	4
340500500100010	5
340500500400010	5
34050100XX0010	10
340501000200010	10
340501000300010	10
340501000600012	10
34050120XX0010	12
340501200400010	12
340501200500010	12
340501200800010	12
340501201500010	12
340501202000010	12
340501201000010	12
340501201200010	12
34050150XX0010	15
340501501500010	15
340501500150010	15
340501500250012	15
340501500400010	15
340501501200010	15
34050200XX0010	20
340502000700010	20

340502000900010	20
340502001000012	20
34050250XX0010	25
340502501000010	25
340502500900010	25
340502501200010	25
340502500600010	25
340502500700010	25
340502502000010	25
34050300XX0010	30
340503000300010	30
340503000400010	30
340503000500010	30
340503000600010	30
340503002000010	30
340503001800010	30
340503002500010	30
340503000700010	30
340503001500010	30
34050400XX0010	40
340504000800010	40
340504001200010	40
340504001000010	40

340504001500012	40
34050500XXX0010	50
340505001200010	50
340505000500010	50
340505000900010	50
340506000800010	60
340506500500010	65
340507000400010	70
340507000500010	70
34050750XXX0010	75
340508000500010	80
340508000600010	80
340508000700010	80
340508000800010	80
340508001000010	80
34051000XXX0010	100
340510000400010	100
340510002000010	100
340512000500010	120
340512000700010	120
34051250XXX0010	125
340512500500010	125
34051500XXX0010	150

Technical data