

## **Quick Release Link for Pear Socket Nemag**

## **Product information**

The Nemag Quick Release Link has been balanced and perfected to become the most reliable, quickest and safest coupling method for ropes and chains. The contact surface of the C-section has been hardened, which considerably lengthens the life span. The construction of the locking piece ensures reliable functioning; even under severe circumstances. The locking pieces are interchangeable.

**Optional:** Nemag also supplies a key especially designed for the Quick Release Link. This key has a hexagonal head that fits into the keyhole of the locking piece. The horizontal handle provides sufficient grip to be able to open or close any locking piece with one short movement. The sharp end of the handel can be used to remove dirt on the outside (of the keyhole).

Marking: According to standard, CE-marked

Standard: EN 1677-1

Warning: The working load is the recommended maximum load for grabbing operations when Quick Release Links and Rope Pear Sockets are passing over a special cable sheave. For other applications a safety factor in line with official international and national guidelines has to be adhered to.

Part Code	Code	WLL	MBL	Weight kg	Delivery time
10.12NQRL04	RL-4	3	25	0.9	15
10.12NQRL05	RL-5	4.5	33	1.2	15
10.12NQRL06	RL-6	5	37.5	1.5	15
10.12NQRL07	RL-7	7	49	2	15
10.12NQRL08	RL-8	8	54	2.5	15
10.12NQRL09	RL-9	9.5	60	3.1	15
10.12NQRL10	RL-10	12	75	4.4	15
10.12NQRL11	RL-11	15	95	5.7	15
10.12NQRL12	RL-12	17	110	7.2	15
10.12NQRL13	RL-13	21	135	8.7	15
10.12NQRL14	RL-14	26	160	11	15
10.12NQRL15	RL-15	30	175	13.5	15
10.12NQRL17	RL-17	42.5	260	23	15

## Blueprint

