
Lifting Solutions Group
Axel Johnson International

Safety Cable Anti-Whiplash

Product information

Adjustable loops with automatic tightening, using sliding sleeves pushed by springs. The length is from the bottom of one loop to the bottom of the other loop. This accessory ensures the safety of individuals by preventing whiplash from hoses that inadvertently disconnect.



- **For a hose with a diameter 20 to 30 mm:** Choose the cable with a diameter of 3.18 mm
- **For a hose with a diameter of 40 to 50 mm:** Choose the cable with a diameter of 4 mm
- **For a hose with a diameter of 50 to 80 mm:** Choose the cable with a diameter of 6.35 mm

... *Read more*

Material: Cable, washers, and compression springs galvanized and aluminum sleeves.
Warning: Do not use for lifting.

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Safety Cable Anti-Whiplash

Technical data

Part code	Rope diameter mm	MBL ton	EWL m	Weight kg
1497RECOR	3.18	0.75	0.43	0.07
1497RETIR	4	1.22	0.6	0.159
1497BESIK	6.35	2.27	1	0.56

Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved