



Transition Link Pewag BWI Stainless

Product information



Stainless steel master link for 1- and 2-leg chainslings.

A higher resistance to acids and caustics compared to the standard transition links G8, G10 and G12 is just one of the many benefits that make this stamped transition link truly remarkable. The use of high-grade stainless steel also ensures that this electrically welded transition and securing link will never rust.

The transition link is part of welded assemblies, may also be used as an end link and is tested at 100 % of its maximum load capacity. Its dimensions are similar to DIN 5688-1.

The outstanding quality of this transition link is also reflected in its wide range of possible applications: It may be used as a connecting link for assembling I- to IV-leg assemblies in welded systems as well as an end link. In addition, it is ideally suited for use in water and wastewater applications and can also be used in connection with chemicals and food products; however, restrictions will apply.

Material: 1.4404 (AISI 316L), 1.4462 (AISI 318LN).

Marking: CE-marked

Finish: Pickled and blasted.

Safety factor: 4:1

Grade: 6

Part Code	Code	WLL ton	WLL 0-45° ton	1-leg	2-leg	d mm	s mm	t mm	w mm	Weight kg	Delivery time
11.0450361	BWI 7-6	0.9	0.9	5/6	5/6	7	-	36	16	0.04	15
11.0450363	BWI 9-6	1.25	1.25	7	7	9	-	44	20	0.07	15
11.0450365	BWI 10-6	1.6	1.6	8	8	10	-	44	20	0.09	15
11.0450367	BWI 13-6	2.5	2.5	10	10	13	10	54	25	0.18	15
11.0450369	BWI 16-6	4.25	4.25	13	13	16	14	70	34	0.35	15
11.0450371	BWI 20-6	6.3	6.3	16	16	20	16	85	40	0.67	15
11.0450029	BWI 22-6	8	8	20	-	23	17	115	50	1.16	15
11.0450374	BWI 26-6	10.07	10.07	-	-	27	20	140	65	1.92	15
11.0460272	BWI 32-6	12	12	26	-	32	26	150	70	3.18	15

Blueprint

