

Lever Hoist Subsea SS19, Tiger

Product information




The Subsea Lever Hoist SS19, has been designed and developed over a number of years for use primarily in subsea, offshore or corrosive environments. The unique design features – including the one piece construction pinion gears and a globally patented Quad Cam Pawl System, along with the superior anti-corrosion properties incorporated in this range, give it significant safety advantages over other lever hoists. This makes the SS19 subsea lever hoist the ideal tool for all marine and extreme applications.

... [Read more](#)

Marking: According to standard
Standard: EN 13157

Lever Hoist Subsea SS19, Tiger

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Number of falls	A mm	B mm	C mm	D mm	E mm	F1 mm mm	F2mm mm
500500080300660	0.8	3	1	128	243	295	158	99	28	45
500500160300660	1.6	3	1	154	370	320	172	104	34	51
500500160150660	1.6	1.5	1	154	370	320	172	104	34	51
500500320300660	3.2	3	1	182	370	400	195	108	36	56
500500630300660	6.3	3	2	242	370	570	195	108	49	70
500500800300660	8	3	3	379	370	580	195	108	51	78
500501000300660	10	3	3	379	370	630	195	108	54	87
500501500300660	15	3	5	566	370	840	195	108	59	81
500502000300660	20	3	6	470	370	1,050	250	160	81	110