

Polyester Fibre Rope, 3-Strand

Product information



Polyester rope to be used as mooring- or anchor-rope on pleasure boats.

Design: Polyester wool reinforced with polyester silk results in an especially soft and knot secure rope.

Specific gravity: 1,38 (sinks).

Melting point: apx 260°C.

Elongation: apx 35%

Material: Polyester has very good resistance against UV-radiation, acids, mild alkalies and rot.

Finish: White.

| Part Code | Diameter mm | Min. Breaking force kN. | Length | Mass g/m | Rope ends | Weight kg/220m | Delivery time |
|------------------|----------------|----------------------------|--------|-------------|------------|-------------------|---------------|
| 12.03PEW080WEC22 | 8 | 8.3 | 220 | 39 | Plain ends | 8,6 | 2 |
| 12.03PEW100WEC22 | 10 | 10.8 | 220 | 60 | Plain ends | 13 | 2 |
| 12.03PEW120WEC22 | 12 | 16.7 | 220 | 90 | Plain ends | 20 | 2 |
| 12.03PEW140WEC22 | 14 | 21.1 | 220 | 118 | Plain ends | 26 | 2 |
| 12.03PEW160WEC22 | 16 | 27.9 | 220 | 160 | Plain ends | 35 | 2 |
| 12.03PEW180WEC22 | 18 | 32.8 | 220 | 195 | Plain ends | 43 | 2 |