



## Polyester Rope, 3-Strand

### Product information

**General:** Polyester rope for typical applications like mooring lines, tie up lines, deck and anchor lines, use in rigging etc.

**Specific gravity:** 1,38 (sinks).

**Melting point:** 265°C.

**Elongation:** 15%.

**Material:** Polyester fibre. It's a smooth and flexible rope, with high strength with excellent resistant to outer and internal wearing. It has a low working elongation and has an excellent UV resista

**Finish:** Black.

| Part code       | Diameter<br>mm | Min. breaking force<br>kN | MBL<br>ton | Length | Colour | Weight<br>kg/110m |
|-----------------|----------------|---------------------------|------------|--------|--------|-------------------|
| 300300803000070 | 8              | 10                        | 1          | 300    | Black  | 5.28              |
| 300301002000070 | 10             | 15.6                      | 1.6        | 200    | Black  | 8.36              |
| 300301201500070 | 12             | 22.5                      | 2.3        | 150    | Black  | 12.1              |
| 300301401300070 | 14             | 31.3                      | 3.2        | 130    | Black  | 16.3              |
| 300301600800070 | 16             | 40.2                      | 4.1        | 80     | Black  | 21.5              |
| 300301801100070 | 18             | 50                        | 5.1        | 110    | Black  | 27                |
| 300302001100070 | 20             | 61.8                      | 6.3        | 110    | Black  | 33.3              |
| 300302201100070 | 22             | 74.5                      | 7.6        | 110    | Black  | 40.4              |

**Technical data**