Lifting Solutions Group
Axel Johnson International

Fast Reeve Crane Blocks 1 sheave

Product information



General:
- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:
- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:
Inquiries for custom versions are welcome!

... *Read more*


Traction Levage
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fast Reeve Crane Blocks 1 sheave

Blueprint



Technical data

Part code	WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 mm	øD2 mm	B mm	O mm	TA mm	TB mm	TLmm mm	L mm	T mm	øZ mm	Weight kg
6097FRB225141125E	12.5	FRB 225 .14 .1 .12,5 .E	14	260 / 225	4	260	225	588	49	345	170	863	970	28	32	90
6097FRB260141125E	12.5	FRB 260 .14 .1 .12,5 .E	14	300 / 260	4	300	260	653	49	400	155	938	1,063	28	32	100
6097FRB260161125E	12.5	FRB 260 .16 .1 .12,5 .E	16	300 / 260	4	300	260	653	49	400	155	938	1,045	28	32	100
6097FRB22514116E	16	FRB 225 .14 .1 .16 .E	14	260 / 225	6	260	225	608	59	345	180	883	1,008	28	32	100
6097FRB26014116E	16	FRB 260 .14 .1 .16 .E	14	300 / 260	6	300	260	693	59	400	165	879	1,103	28	32	120
6097FRB26016116E	16	FRB 260 .16 .1 .16 .E	16	300 / 260	6	300	260	693	59	400	165	978	1,103	28	32	120
6097FRB28516116E	16	FRB 285 .16 .1 .16 .E	16	320 / 285	6	320	285	723	59	420	165	1,023	1,148	28	32	135
6097FRB35516116E	16	FRB 355 .16 .1 .16 .E	16	410 / 355	6	410	355	788	59	500	195	1,133	1,258	28	32	180
6097FRB35519116EA	16	FRB 355 .19 .1 .16 .E .A	19	410 / 355	6	410	355	788	59	500	195	1,133	1,263	35	37	180
6097FRB35519116EB	16	FRB 355 .19 .1 .16 .E .B	19	410 / 355	6	410	355	788	59	500	215	1,133	1,263	35	37	225
6097FRB26014120E	20	FRB 260 .14 .1 .20 .E	14	300 / 260	8	300	260	748	69	400	165	1,033	1,168	28	32	130
6097FRB26016120E	20	FRB 260 .16 .1 .20 .E	16	300 / 260	8	300	260	748	69	400	165	1,033	1,168	28	32	130
6097FRB28516120E	20	FRB 285 .16 .1 .20 .E	16	320 / 285	8	320	285	778	69	420	165	1,078	1,213	28	32	160
6097FRB32016120E	20	FRB 320 .16 .1 .20 .E	16	365 / 320	8	365	320	768	69	450	180	1,101	1,236	28	32	160
6097FRB35516120E	20	FRB 355 .16 .1 .20 .E	16	410 / 355	8	410	355	853	69	500	223	1,198	1,333	28	32	250
6097FRB35519120E	20	FRB 355 .19 .1 .20 .E	19	410 / 355	8	410	355	853	69	500	225	1,198	1,338	35	37	250
6097FRB40019125E	25	FRB 400 .19 .1 .25 .E	19	460 / 400	8	460	400	883	69	570	220	1,258	1,398	35	37	275
6097FRB40022125E	25	FRB 400 .22 .1 .25 .E	22	460 / 400	8	460	400	883	69	570	220	1,258	1,403	40	43	275
6097FRB40022129E	29	FRB 400 .22 .1 .29 .E	22	460 / 400	8	460	400	883	69	570	270	1,268	1,413	40	43	365
6097FRB45026132EA	32	FRB 450 .26 .1 .32 .E .A	26	515 / 450	10	515	450	1,003	79	600	250	1,426	1,593	45	52	450

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fast Reeve Crane Blocks 1 sheave

Technical data

Part code	WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 mm	øD2 mm	B mm	O mm	TA mm	TB mm	TLmm mm	L mm	T mm	øZ mm	Weight kg
6097FRB45022132E	32	FRB 450 .22 .1 .32 .E	22	515 / 450	10	515	450	1,003	76	600	250	1,416	1,572	40	43	455
6097FRB45024132EA	32	FRB 450 .24 .1 .32 .E .A	24	515 / 450	10	515	450	1,003	76	600	250	1,426	1,592	45	52	455
6097FRB45024132EB	32	FRB 450 .24 .1 .32 .E .B	24	515 / 450	10	515	450	1,003	76	600	333	1,426	1,292	45	52	590
6097FRB45026132EB	32	FRB 450 .26 .1 .32 .E .B	26	515 / 450	10	515	450	1,003	79	600	333	1,426	1,593	45	52	590
6097FRB45022140E	40	FRB 450 .22 .1 .40 .E	22	515 / 450	12	515	450	1,074	84	600	333	1,487	1,655	40	43	590
6097FRB45024140E	40	FRB 450 .24 .1 .40 .E	24	515 / 450	12	515	450	1,074	84	600	333	1,497	1,675	45	52	590
6097FRB45026140E	40	FRB 450 .26 .1 .40 .E	26	515 / 450	12	515	450	1,074	84	600	333	1,497	1,675	45	52	590
6097FRB52824140E	40	FRB 528 .24 .1 .40 .E	24	595 / 528	12	595	528	1,114	84	710	323	1,592	1,770	45	52	680
6097FRB52826140E	40	FRB 528 .26 .1 .40 .E	26	595 / 528	12	595	528	1,114	84	710	323	1,592	1,770	45	52	680
6097FRB52828140E	40	FRB 528 .28 .1 .40 .E	28	595 / 528	12	595	528	1,114	84	710	323	1,593	1,780	50	59	680
6097FRB57526140E	40	FRB 575 .26 .1 .40 .E	26	650 / 575	12	650	575	1,138	84	770	313	1,642	1,821	45	52	750
6097FRB45026150EA	50	FRB 450 .26 .1 .50 .E .A	26	515 / 450	16	515	450	1,094	87	600	333	1,514	1,706	45	52	590
6097FRB45026150EB	50	FRB 450 .26 .1 .50 .E .B	26	515 / 450	16	515	450	1,094	87	600	3,363	1,514	1,706	45	52	680
6097FRB52824150E	50	FRB 528 .24 .1 .50 .E	24	595 / 528	16	595	528	1,111	97	710	343	1,589	1,781	45	52	750
6097FRB52826150E	50	FRB 528 .26 .1 .50 .E	26	595 / 528	16	595	528	1,111	97	710	343	1,589	1,781	45	52	750
6097FRB52828150E	50	FRB 528 .28 .1 .50 .E	28	595 / 528	16	595	528	1,111	97	710	343	1,589	1,791	50	59	750
6097FRB57528150E	50	FRB 575 .28 .1 .50 .E	28	650 / 575	16	650	575	1,144	97	770	313	1,649	1,851	50	59	750
6097FRB63028150E	50	FRB 630 .28 .1 .50 .E	28	710 / 630	16	710	630	1,172	97	830	323	1,717	1,919	50	59	975
6097FRB57532163E	63	FRB 575 .32 .1 .63 .E	32	650 / 575	16	650	575	1,223	97	770	352	1,738	1,945	60	66	975
6097FRB63032163E	63	FRB 630 .32 .1 .63 .E	32	710 / 630	16	710	630	1,253	97	830	323	1,798	2,005	60	66	975
6097FRB67028163E	63	FRB 670 .28 .1 .63 .E	28	760 / 670	16	760	670	1,248	97	870	453	1,813	2,015	50	59	1,800
6097FRB67032163E	63	FRB 670 .32 .1 .63 .E	32	760 / 670	16	760	670	1,248	97	870	453	1,813	2,020	60	66	1,800

© November 2026 - All Rights Reserved