



General use



Winch rope



Stay rope



Agriculture and livestock



Slings



Steel Wire Rope ROPETEX S33 Stainless Steel

Product information

ROPETEX


Steel wire rope ROPETEX S33 in stainless steel is a good choice for basic lifting applications in environments where corrosion resistance is important.

ROPETEX S33 is equipped with a Wire Strand Core (WSC) which gives the rope a good strength and a reasonable balance between fatigue and wear resistance.

ROPETEX S33 can be used for applications where the rope runs over sheaves or is spooled on a drum.

Typical applications:

- lifting applications
- slings
- winch rope
- stay ropes

Rope construction: 6x19M-WSC

Material: AISI316 / EN 1.4401

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-4

except material

Fill factor: 0,53

Part Code	Rope Diameter, mm	Steel area mm ²	Min. Breaking force kN. 1570 N/mm ²	Weight kg/100m
171383	2	1.67	2.27	1.52
171384	3	3.76	5.12	3.43
171385	4	6.69	9.09	6.1
171386	5	10.5	14.2	9.53
171387	6	15	20.5	13.7
171388	7	20.5	27.8	18.7
171389	8	26.8	36.4	24.4
171390	10	41.8	56.8	38.1
171391	12	60.2	81.8	54.9
108101404620038	14	81.9	111	74.7
108101604620038	16	107	145	97.5