



## DNV Master Link Grade 8 P-6810

### Product information

The Green Pin<sup>®</sup> DNV Master Link is perfect for offshore use. The Master Link is DNV-certified and has a large opening to accommodate larger lifting points and crane hooks. Moreover, the coating of the DNV Master Link ensures long-term durability, even under severe environmental conditions. The DNV Master Link is available in a range with a working load limit from 4.1 up to 100 ton.

**Material:** Alloy steel, Grade 8

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** DNV 2.7-1 Approved, EN 1677-4

**Safety factor:** 5:1

**Grade:** 8

| <b>Part code</b> | <b>WLL<br/>ton</b> | <b>a<br/>mm</b> | <b>b<br/>mm</b> | <b>c<br/>mm</b> | <b>Weight<br/>kg</b> |
|------------------|--------------------|-----------------|-----------------|-----------------|----------------------|
| 401100410480     | 4.1                | 16              | 150             | 75              | 0.68                 |
| 401100700480     | 7                  | 22              | 270             | 140             | 2.28                 |
| 401100930480     | 9.3                | 26              | 270             | 140             | 3.11                 |
| 401101450480     | 14.5               | 28              | 270             | 140             | 3.78                 |
| 401101900480     | 19                 | 32              | 270             | 140             | 5.02                 |
| 401101950480     | 19.5               | 28              | 200             | 110             | 3                    |
| 401102600480     | 26                 | 36              | 270             | 140             | 6.46                 |
| 401103050480     | 30.5               | 40              | 280             | 155             | 8.46                 |
| 401104000480     | 40                 | 45              | 320             | 175             | 12.2                 |
| 401105100480     | 51                 | 50              | 350             | 195             | 16.5                 |
| 401107500480     | 75                 | 65              | 410             | 220             | 33                   |
| 401110000480     | 100                | 75              | 450             | 250             | 49                   |

## Blueprint

